

EDURING FUNCTION AND TRANSVERSAL APPROACH

Both Enduring Function and Transversal Approach are inspired by boldly contrasted layers of striated lines forming subtle geometric patterns that are sure to create dynamic commercial spaces. Vibrant and durable, these styles will inspire creativity and stand up to high traffic areas.

ENDURING FUNCTION

ProductType Broadloom
Construction Tufted

Surface Appearance Textured Patterned Loop

Gauge 1/12" (47.00 rows per 10 cm)

 Tufted Weight
 16 oz/yd² (542 g/m²)

 Pile Thickness
 .103" (2.62 mm)

 Stitches Per Inch
 12.0 (47.24 per 10 cm)

Density 5,592 Weight Density 89,475

Dye Method100% Solution DyedFiberTypeColorstrand® SD Nylon

 Stain Release Technology
 Mohawk Protection Plus Stain

 Soil Release Technology
 Mohawk Protection Plus Soil

Primary Backing Woven Polypropylene
Secondary Backing Weldlok® Plus

Recycled Content Contains 31% pre-consumer recycled content

by total product weight

NSF 140 Gold

Pattern Repeat $18" \text{ (W)} \times 28.83" \text{ (L)}$

Indoor Air Quality Green Label Plus Certified # 3802

Size/Width 12" width (3.66m)

Flammability ASTM E 648 Class 1 (Glue Down)
Smoke Density ASTM E 662 Less than 450

Appearance Retention Rating (TARR) Heavy Traffic

Warranties

Lifetime Limited Wear Warranty
Lifetime Limited Edge Ravel, Zippering,
Delamination and Dimesional Stability Warranty
Lifetime Limited Static Protection Warranty
Lifetime Limited Colorfastness to Light Warranty
10 Year Limited Stain Resistance Warranty
10 Year Limited Colorfastness to Atmospheric

Contaminants Warranty

AATCC-134 Under 3.5 KV

TRANSVERSAL APPROACH

Broadloom Tufted

Textured Patterned Loop 1/12" (47.00 rows per 10 cm)

16 oz/yd² (542 g/m²) .118" (3.00 mm) 12.0 (47.24 per 10 cm)

4,881 78,101

100% Solution Dyed Colorstrand® SD Nylon

Mohawk Protection Plus Stain Mohawk Protection Plus Soil

Woven Polypropylene

Weldlok®Plus

Contains 31% pre-consumer recycled content

by total product weight

Gold

18" (W) x 17.75" (L)

Green Label Plus Certified # 3802

12" width (3.66m)

ASTM E 648 Class 1 (Glue Down) ASTM E 662 Less than 450 AATCC-134 Under 3.5 KV

Heavy Traffic

Lifetime Limited Wear Warranty
Lifetime Limited Edge Ravel, Zippering,
Delamination and Dimesional Stability Warranty
Lifetime Limited Static Protection Warranty
Lifetime Limited Colorfastness to Light Warranty
10 Year Limited Stain Resistance Warranty
10 Year Limited Colorfastness to Atmospheric

Contaminants Warranty

Cover: Enduring Function 521 Limitless Potential and Transversal Approach 521 Limitless Potential

Enduring Function

Static Propensity



521 Limitless Potential



589
Transcending Journey



841 Fresh Perspective



858 Totally Unexpected



869 Innovative Forecast



878 Uniquely Inspiring



979 Channeling Insight

Transversal Approach



521 Limitless Potential



589 Transcending Journey



841 Fresh Perspective



858 Totally Unexpected



869 Innovative Forecast



878 Uniquely Inspiring



979 Channeling Insight



Up to 2,000 sq. yds. available within 10 business days or less

COLORSTRANDSD

