



SURFACE PURPOSE



DISTINCTIVE APPEAL

### SURFACE PURPOSE AND DISTINCTIVE APPEAL

Ideal for spaces where performance and function are important, Surface Purpose and Distinctive Appeal are highly durable while offering bold visual aesthetics. Together these styles create the perfect balance for refined interiors.

## SURFACE PURPOSE

Product Type	Broadloom
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	16 oz/yd <sup>2</sup> (542 g/m <sup>2</sup> )
Pile Thickness	.098" (2.49 mm)
Stitches Per Inch	13.0 (51.18 per 10 cm)
Density	5,877
Weight Density	94,040
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Woven Polypropylene
Secondary Backing	Weldlok® Plus
Recycled Content	Contains 31% pre-consumer recycled content by total product weight
NSF 140	Gold
Pattern Repeat	18" (W) x 18.46" (L)
Indoor Air Quality	Green Label Plus Certified # 3802
Size/Width	12" width (3.66m)
Flammability	ASTM E 648 Class 1 (Glue down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

## DISTINCTIVE APPEAL

Product Type	Broadloom
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Tufted Weight	16 oz/yd <sup>2</sup> (542 g/m <sup>2</sup> )
Pile Thickness	.081" (2.05 mm)
Stitches Per Inch	11.7 (46.06 per 10 cm)
Density	7,111
Weight Density	113,777
Dye Method	100% Solution Dyed
Fiber Type	Colorstrand® SD Nylon
Stain Release Technology	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil
Primary Backing	Woven Polypropylene
Secondary Backing	Weldlok® Plus
Recycled Content	Contains 31% pre-consumer recycled content by total product weight
NSF 140	Gold
Pattern Repeat	18" (W) x 27.05" (L)
Indoor Air Quality	Green Label Plus Certified # 3802
Size/Width	12" width (3.66m)
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC-134 Under 3.5 KV
Appearance Retention Rating (TARR)	Heavy Traffic
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants Warranty

Cover: Surface Purpose 869 Vivid Vision and Distinctive Appeal 869 Vivid Vision

### Surface Purpose



521  
Classic Evolution



589  
Unique Adaptation



841  
Original Impact



858  
Enticing Texture



869  
Vivid Vision



878  
Monumental Canvas



979  
Sensory Touch

### Distinctive Appeal



521  
Classic Evolution



589  
Unique Adaptation



841  
Original Impact



858  
Enticing Texture



869  
Vivid Vision



878  
Monumental Canvas



979  
Sensory Touch



Up to 2,000 sq. yds. available within 10 business days or less

