



AMITY TILE



COMPOUND TILE



GUILD TILE



RAPPORT TILE

TEAMWORK COLLECTION

The Teamwork Collection was designed for bold and demanding interiors. These four complementary styles are the perfect counterparts for creating visual interest throughout an entire commercial space.

AMITY TILE

COMPOUND TILE

GUILD TILE

RAPPORT TILE

Style Number	2B107	2B67	2B110	2B111
Product Type	Tile	Tile	Tile	Tile
Construction	Tufted	Tufted	Tufted	Tufted
Surface Appearance	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)	1/12" (47.00 rows per 10 cm)	1/12" (47.00 rows per 10 cm)	1/12" (47.00 rows per 10 cm)
Density	6,442	6,059	4,896	7,200
Dye Method	Solution Dyed/Yarn Dyed	Solution Dyed/Yarn Dyed	Solution Dyed/Yarn Dyed	Solution Dyed/Yarn Dyed
Fiber Type	Colorstrand® Nylon	Colorstrand® Nylon	Colorstrand® Nylon	Colorstrand® Nylon
Stain Release Technology	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil
Primary Backing	Non-Woven Synthetic	Non-Woven Synthetic	Non-Woven Synthetic	EcoFlex ICT
Secondary Backing	UltraSet®	UltraSet®	UltraSet®	UltraSet®
Indoor Air Quality	Green Label Plus Certified # 1098	Green Label Plus Certified # 1098	Green Label Plus Certified # 1098	Green Label Plus Certified # 1098
Size	24" x 24" (.6096 m x .6096 m)	24" x 24" (.6096 m x .6096 m)	24" x 24" (.6096 m x .6096 m)	24" x 24" (.6096 m x .6096 m)
Flammability	ASTM E 648 Class 1 (Glue down)	ASTM E 648 Class 1 (Glue down)	ASTM E 648 Class 1 (Glue down)	ASTM E648 Class 1 (Glue down)
Smoke Density	ASTM E 662 Less than 450	ASTM E 662 Less than 450	ASTM E 662 Less than 450	ASTM E 662 Less than 450
Static Propensity	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV
Warranties	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability 10 Year Limited Stain Resistance	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability 10 Year Limited Stain Resistance	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability 10 Year Limited Stain Resistance	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability 10 Year Limited Stain Resistance

Cover: Amity Tile 989 Black Velvet, Compound Tile 989 Black Velvet, Guild Tile 989 Black Velvet with Choice Step LVT P006S Dovetail Gray, Rapport Tile 989 Black Velvet

Compound



131
Madras



878
Mudslide



968
Smoky Martin



585
Sea Breeze



989
Black Velvet



Up to 2,000 sq. yds. available within 10 business days or less

colorSTRAND
The Premium Synthetic Fiber Commercial Floor