

ASTONISHING VIEW 2B47

PRODUCT SPECIFICATIONS

PRODUCT TYPE	Broadloom
CONSTRUCTION	Tufted
SURFACE APPEARANCE	Textured Pattern Loop
GAUGE	1/10" (39.37 rows per 10 cm)
PILE WEIGHT	22 oz/yd2 (746 g/m2)
PILE THICKNESS	.117" (2.97 mm)
STITCHES PER INCH	11.3 (44.49 per 10 cm)
DYE METHOD	75% Solution Dyed / 22% Yarn Dyed
FIBER TYPE	Colorstrand® Nylon
STAIN RELEASE TECHNOLOGY	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY	Mohawk Protection Plus Soil
DENSITY	6,769
WEIGHT DENSITY	148,918
PRIMARY BACKING	Woven Polypropylene
SECONDARY BACKING	Weldlock®
PATTERN REPEAT	1.2" (W) x 106" (L)
WIDTH	12' width (3.66 m)
FLAMMABILITY	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY	ASTM E 662 Less than 450
STATIC PROPENSITY	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS	8216
APPEARANCE RETENTION RATING	Severe Traffic
WARRANTIES	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Limited 10-Year Stain Resistance (Food and Beverage Only)

All specifications are subject to normal manufacturing tolerances.

6/18