

# CAPITAL PORT 1Q42

## PRODUCT SPECIFICATIONS

<b>PRODUCT TYPE:</b>	Broadloom
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Enhanced Loop Graphic
<b>GAUGE:</b>	1/10" (39.37 rows per 10 cm)
<b>TUFTED WEIGHT:</b>	26 oz/yd <sup>2</sup> (882 g/m <sup>2</sup> )
<b>PILE THICKNESS:</b>	.193" (4.90 mm)
<b>STITCHES PER INCH:</b>	10.0 (39.37 per 10 cm)
<b>DYE METHOD:</b>	100% Solution Dyed
<b>FIBER TYPE:</b>	Permastrand® Olefin
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	4,757
<b>WEIGHT DENSITY:</b>	123,682
<b>PRIMARY BACKING:</b>	Woven Polypropylene
<b>SECONDARY BACKING:</b>	Weldlok®
<b>NSF 140</b>	Gold
<b>PATTERN REPEAT:</b>	1.2" (W) x 1.6" (L)
<b>WIDTH:</b>	12" width (3.66 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class II (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	Certified 3878
<b>APPEARANCE RETENTION RATING (TARR):</b>	Heavy Traffic
<b>WARRANTIES:</b>	<ul style="list-style-type: none"> <li>10 Year Limited Wear Warranty</li> <li>10 Year Limited Static Protection</li> <li>10 Year Limited Stain Resistance Warranty</li> <li>10 Year Limited Colorfastness to Light</li> <li>10 Year Limited Colorfastness to Atmospheric Contaminants</li> </ul>