

CHEX 6343

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Loop Pile Graphic
GAUGE:	1/10" (39.37 rows per 10 cm)
TUFTED WEIGHT:	23 oz/yd² (780 g/m²)
PILE THICKNESS:	.155" (3.94 mm)
STITCHES PER INCH:	8.0 (31.50 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Permastrand® Polypropylene
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	5,342
WEIGHT DENSITY:	122,866
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok®
NSF 140	Gold
PATTERN REPEAT:	0.4" (W) × 0.5" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class II (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 3878
APPEARANCE RETENTION RATING (TARR):	Heavy Traffic
WARRANTIES:	10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants