

CLOISONNÉ II 5342

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Loop Pile Graphic
GAUGE:	1/10" (39.37 rows per 10 cm)
TUFTED WEIGHT:	28 oz/yd ² (949 g/m ²)
PILE THICKNESS:	.140" (3.56 mm)
STITCHES PER INCH:	10.0 (39.37 per 10 cm)
DYE METHOD:	65% Solution Dyed / 35% Yarn Dyed
FIBER TYPE:	Colorstrand® Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	5,200
WEIGHT DENSITY:	140,400
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok®
NSF 140	Gold
PATTERN REPEAT:	1.4" (W) x 4" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 8216
APPEARANCE RETENTION RATING (TARR):	Severe Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty 10 Year Limited Stain Resistance Warranty (Food & Beverage Only)