

DEFENDER 20 / 26 | 6350 / 6355 / 6355T

PRODUCT SPECIFICATIONS

	DEFENDER 20 6350	DEFENDER 26 6355	DEFENDER 26 6355T
PRODUCT TYPE:	Broadloom	Broadloom	Broadloom
CONSTRUCTION:	Tufted	Tufted	Tufted
SURFACE APPEARANCE:	Level Loop	Level Loop	Level Loop
GAUGE:	1/10" (39.37 rows per 10 cm)	1/10" (39.37 rows per 10 cm)	1/10" (39.37 rows per 10 cm)
TUFTED WEIGHT:	20 oz/yd ² (678 g/m ²)	26 oz/yd ² (882 g/m ²)	26 oz/yd ² (882 g/m ²)
PILE THICKNESS:	.140" (3.56 mm)	.163" (4.14 mm)	.163" (4.14 mm)
STITCHES PER INCH:	9.6 (37.80 per 10 cm)	11.5 (45.28 per 10 cm)	11.5 (45.28 per 10 cm)
DYE METHOD:	100% Solution Dyed	100% Solution Dyed	100% Solution Dyed
FIBER TYPE:	Permastrand® Polypropylene	Permastrand® Polypropylene	Permastrand® Polypropylene
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil
DENSITY:	5,220	5,885	5,885
WEIGHT DENSITY:	104,400	153,010	153,010
PRIMARY BACKING:	Woven Polypropylene	Woven Polypropylene	Woven Polypropylene
SECONDARY BACKING:	Weldlok®	Weldlok®	Weldlok® Unitary
NSF 140:	Gold	Gold	Gold
PATTERN REPEAT:	None	None	None
WIDTH:	12" width (3.66 m) & 15" width (4.572 m)	12" width (3.66 m) & 15" width (4.572 m)	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class II (Glue Down)	ASTM E 648 Class II (Glue Down)	ASTM E 648 Class II (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450	ASTM E 662 Less than 450	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV	AATCC-134 Under 3.5 KV	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 3878	Certified 3878	Certified 3878
APPEARANCE RETENTION RATING (TARR):	Moderate Traffic	Moderate Traffic	Moderate Traffic
WARRANTIES:	10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants	10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants	10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants