

DESIGN MEDLEY TILE 1T79

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Carpet Tile
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Textured Patterned Loop
GAUGE:	1/12" (47.00 rows per 10 cm)
TUFTED WEIGHT:	22 oz/yd ² (746 g/m ²)
PILE THICKNESS:	.109" (2.77 mm)
STITCHES PER INCH:	9.0 (35.43 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Colorstrand® SD Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	7,226
WEIGHT DENSITY:	159,852
PRIMARY BACKING:	Non-Woven Synthetic
SECONDARY BACKING:	UltraSet®
RECYCLED CONTENT:	Contains a minimum 39% pre-consumer recycled content by total product weight
NSF 140	Gold
INSTALLATION METHOD:	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
SIZE:	24" x 24" (.6096 m x .6096 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 1098
APPEARANCE RETENTION RATING (TARR):	Severe Traffic
WARRANTIES:	<p>Lifetime Limited Wear Warranty</p> <p>Lifetime Limited Static Protection</p> <p>Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty</p> <p>Lifetime Limited Colorfastness to Light Warranty</p> <p>10 Year Limited Stain Resistance Warranty</p> <p>10 Year Limited Colorfastness to Atmospheric Contaminants</p>