

FILIGREE 778

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Loop Pile Graphic
GAUGE:	1/10" (39.37 rows per 10 cm)
TUFTED WEIGHT:	26 oz/yd ² (848 g/m ²)
PILE THICKNESS:	.160" (4.06 mm)
STITCHES PER INCH:	9.0 (35.43 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Permastrand® Polypropylene
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	5,850
WEIGHT DENSITY:	152,100
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok®
NSF 140	Gold
PATTERN REPEAT:	1.8" (W) x 4.5" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class II (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 3878
APPEARANCE RETENTION RATING (TARR):	Heavy Traffic
WARRANTIES:	<ul style="list-style-type: none"> 10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants