

GUILD 2B110

PRODUCT TYPE:	Carpet Tile
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Textured Patterned Loop
GAUGE:	1/12" (47.00 rows per 10 cm)
PILE WEIGHT:	17 oz/yd ² (546 g/m ²)
PILE THICKNESS:	.125" (3.18 mm)
STITCHES PER INCH:	11.9 (45.28 per 10 cm)
DYE METHOD:	42% Solution Dyed / 58% Yarn Dyed
FIBER TYPE:	Colorstrand® Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	4,896
WEIGHT DENSITY:	83,232
PRIMARY BACKING:	Non-Woven Synthetic
SECONDARY BACKING:	Ultraset®
RECYCLED CONTENT:	Contains a minimum 39% pre-consumer recycled content by total product weight
NSF 140	Gold
INSTALLATION METHOD:	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
SIZE:	24" x 24" (.6096 m x .6096 m)
FLAMMABILITY:	ASTM E 648 Class 1 (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	1098
CRI APPEARANCE RETENTION RATING:	Heavy Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty 10 Year Limited Stain Resistance Warranty (Food & Beverage Only)