

# MAJOR FACTOR TILE 1Y13

## PRODUCT SPECIFICATIONS

<b>PRODUCT TYPE:</b>	Carpet Tile
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Textured Loop
<b>GAUGE:</b>	1/8" (31.50 rows per 10 cm)
<b>TUFTED WEIGHT:</b>	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )
<b>PILE THICKNESS:</b>	.116" (2.95 mm)
<b>STITCHES PER INCH:</b>	9.8 (38.58 per 10 cm)
<b>DYE METHOD:</b>	100% Solution Dyed
<b>FIBER TYPE:</b>	Colorstrand® SD Nylon
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	6,207
<b>WEIGHT DENSITY:</b>	124,140
<b>PRIMARY BACKING:</b>	Non-Woven Synthetic
<b>SECONDARY BACKING:</b>	UltraSet®
<b>RECYCLED CONTENT:</b>	Contains a minimum 39% pre-consumer recycled content by total product weight
<b>NSF 140</b>	Gold
<b>INSTALLATION METHOD:</b>	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn
<b>SIZE:</b>	24" x 24" (.6096 m x .6096 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class I (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	Certified 1098
<b>APPEARANCE RETENTION RATING (TARR):</b>	Heavy Traffic
<b>WARRANTIES:</b>	<p>Lifetime Limited Wear Warranty</p> <p>Lifetime Limited Static Protection Warranty</p> <p>Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty</p> <p>Lifetime Limited Colorfastness to Light Warranty</p> <p>10 Year Limited Stain Resistance Warranty</p> <p>10 Year Limited Colorfastness to Atmospheric Contaminants</p>