

# METRO GRID 1M47

## PRODUCT SPECIFICATIONS

<b>PRODUCT TYPE:</b>	Broadloom
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Patterned Cut and Loop
<b>GAUGE:</b>	1/12" (47.00 rows per 10 cm)
<b>TUFTED WEIGHT:</b>	28 oz/yd <sup>2</sup> (949 g/m <sup>2</sup> )
<b>PILE THICKNESS:</b>	.164" (4.17 mm)
<b>STITCHES PER INCH:</b>	11.6 (45.67 per 10 cm)
<b>DYE METHOD:</b>	100% Solution Dyed
<b>FIBER TYPE:</b>	Colorstrand® SD Nylon
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	5,635
<b>WEIGHT DENSITY:</b>	157,780
<b>PRIMARY BACKING:</b>	Woven Polypropylene
<b>SECONDARY BACKING:</b>	Weldlok®
<b>NSF 140:</b>	Gold
<b>PATTERN REPEAT:</b>	1.0" (W) x 1.0" (L)
<b>WIDTH:</b>	12" width (3.66 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class I (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	Certified 8216
<b>APPEARANCE RETENTION RATING (TARR):</b>	Heavy Traffic
<b>WARRANTIES:</b>	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

*All specifications are subject to normal manufacturing tolerances. 7/15  
For additional technical information, please contact Technical Services at 800.833.6954.*