

OLYMPIC MEDAL 1G29

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Enhanced Loop Graphic
GAUGE:	1/10" (39.37 rows per 10 cm)
TUFTED WEIGHT:	20 oz/yd ² (678 g/m ²)
PILE THICKNESS:	.157" (3.99 mm)
STITCHES PER INCH:	13.3 (52.36 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Colorstrand® SD Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	4,586
WEIGHT DENSITY:	91,720
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok®
NSF 140:	Gold
PATTERN REPEAT:	4.8" (W) x 1.8" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 8216
APPEARANCE RETENTION RATING (TARR):	Heavy Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants

*All specifications are subject to normal manufacturing tolerances. 7/15
For additional technical information, please contact Technical Services at 800.833.6954.*