

## RAPPORT 2B111

<b>PRODUCT TYPE:</b>	Carpet Tile
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Textured Patterned Loop
<b>GAUGE:</b>	1/12" (47.00 rows per 10 cm)
<b>PILE WEIGHT:</b>	17 oz/yd <sup>2</sup> (546 g/m <sup>2</sup> )
<b>PILE THICKNESS:</b>	.110" (2.79 mm)
<b>STITCHES PER INCH:</b>	11.5 (45.28 per 10 cm)
<b>DYE METHOD:</b>	42% Solution Dyed / 58% Yarn Dyed
<b>FIBER TYPE:</b>	Colorstrand® Nylon
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	5,563
<b>WEIGHT DENSITY:</b>	94,581
<b>PRIMARY BACKING:</b>	Non-Woven Synthetic
<b>SECONDARY BACKING:</b>	Ultraset®
<b>RECYCLED CONTENT:</b>	Contains a minimum 39% pre-consumer recycled content by total product weight
<b>NSF 140</b>	Gold
<b>INSTALLATION METHOD:</b>	Monolithic / Vertical Ashlar / Brick Ashlar / Quarter Turn / Multi Directional
<b>SIZE:</b>	24" x 24" (.6096 m x .6096 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class 1 (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	1098
<b>CRI APPEARANCE RETENTION RATING:</b>	Heavy Traffic
<b>WARRANTIES:</b>	Lifetime Limited Wear Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Edge Ravel, Zippering, Delamination, and Dimensional Stability Warranty 10 Year Limited Stain Resistance Warranty (Food & Beverage Only)