

SURFACE PURPOSE 2B75

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Textured Patterned Loop
GAUGE:	1/12" (47.00 rows per 10 cm)
TUFTED WEIGHT:	16 oz/yd ² (542 g/m ²)
PILE THICKNESS:	.098" (2.49 mm)
STITCHES PER INCH:	13.0 (51.18 per 10 cm)
DYE METHOD:	100% Solution Dyed
FIBER TYPE:	Colorstrand® SD Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	5,877
WEIGHT DENSITY:	94,040
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok® Plus
RECYCLED CONTENT:	Contains 31% pre-consumer recycled content by total product weight
NSF 140	Gold
PATTERN REPEAT:	18" (W) x 18.46" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 3802
APPEARANCE RETENTION RATING (TARR):	Heavy Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Edge Ravel, Zippering, Delamination and Dimensional Stability Warranty Lifetime Limited Static Protection Warranty Lifetime Limited Colorfastness to Light Warranty 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants