

TOWN CRIER II 1E66

PRODUCT SPECIFICATIONS

PRODUCT TYPE:	Broadloom
CONSTRUCTION:	Tufted
SURFACE APPEARANCE:	Cut / Uncut
GAUGE:	1/8" (31.50 rows per 10 cm)
TUFTED WEIGHT:	28 oz/yd ² (949 g/m ²)
PILE THICKNESS:	.265" (6.73 mm)
STITCHES PER INCH:	13.0 (51.18 per 10 cm)
DYE METHOD:	Piece Dyed
FIBER TYPE:	ColorStrand [®] Nylon
STAIN RELEASE TECHNOLOGY:	Mohawk Protection Plus Stain
SOIL RELEASE TECHNOLOGY:	Mohawk Protection Plus Soil
DENSITY:	3,804
WEIGHT DENSITY:	106,512
PRIMARY BACKING:	Woven Polypropylene
SECONDARY BACKING:	Weldlok [®]
NSF 140:	Gold
PATTERN REPEAT:	0.5" (W) x .875" (L)
WIDTH:	12" width (3.66 m)
FLAMMABILITY:	ASTM E 648 Class I (Glue Down)
SMOKE DENSITY:	ASTM E 662 Less than 450
STATIC PROPENSITY:	AATCC-134 Under 3.5 KV
IAQ GREEN LABEL PLUS:	Certified 6678
APPEARANCE RETENTION RATING (TARR):	Moderate Traffic
WARRANTIES:	Lifetime Limited Wear Warranty Lifetime Limited Static Protection