

# UNPLUGGED 2B51

## PRODUCT SPECIFICATIONS

<b>PRODUCT TYPE:</b>	Broadloom
<b>CONSTRUCTION:</b>	Tufted
<b>SURFACE APPEARANCE:</b>	Graphic Loop
<b>GAUGE:</b>	1/10" (39.37 rows per 10 cm)
<b>TUFTED WEIGHT:</b>	16 oz/yd <sup>2</sup> (542 g/m <sup>2</sup> )
<b>PILE THICKNESS:</b>	.143" (3.63 mm)
<b>STITCHES PER INCH:</b>	8.2 (32.28 per 10 cm)
<b>DYE METHOD:</b>	100% Solution Dyed
<b>FIBER TYPE:</b>	Permastrand® Polypropylene
<b>STAIN RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Stain
<b>SOIL RELEASE TECHNOLOGY:</b>	Mohawk Protection Plus Soil
<b>DENSITY:</b>	4,028
<b>WEIGHT DENSITY:</b>	64,448
<b>PRIMARY BACKING:</b>	Woven Polypropylene
<b>SECONDARY BACKING:</b>	Weldlok®
<b>NSF 140:</b>	Gold
<b>PATTERN REPEAT:</b>	1.2" (W) x 1.9" (L)
<b>WIDTH:</b>	12" width (3.66 m)
<b>FLAMMABILITY:</b>	ASTM E 648 Class II (Glue Down)
<b>SMOKE DENSITY:</b>	ASTM E 662 Less than 450
<b>STATIC PROPENSITY:</b>	AATCC-134 Under 3.5 KV
<b>IAQ GREEN LABEL PLUS:</b>	Certified 3878
<b>CRI APPEARANCE RETENTION RATING:</b>	Moderate Traffic
<b>WARRANTIES:</b>	10 Year Limited Wear Warranty 10 Year Limited Static Protection 10 Year Limited Stain Resistance Warranty 10 Year Limited Colorfastness to Light Warranty 10 Year Limited Colorfastness to Atmospheric Contaminants