

**Mohawk**  
**NuBroadlok Premium Plus Adhesive**  
**R0020**



**NuBroadlok Premium Plus Multi-Purpose Adhesive** is a fast-grabbing, high solids, commercial carpet premium grade latex adhesive for use with all Aladdin Commercial carpets. Choose this adhesive for carpet backed with unitary, ActionBac, or attached cushion. This low odor adhesive provides quick tack as well as excellent re-tack properties. NuBroadlok is CRI Green Label Plus approved.

**Installation Instructions:** The floor must be sound, smooth, dry and clean. Remove any dirt, wax, loose paint, and foreign material that would interfere with a good bond. Seal porous or dusty concrete surfaces with Mohawk PrimeCoat sealer. When installing over a non-porous surface, let the adhesive become tacky (1" – 2" legs when finger tested).

**Substrates & Site Conditions:** Apply NuBroadlok over smooth above, on, or below grade concrete, APA grade underlayment plywood, Terrazzo, polymer-fortified Portland cement underlayment, and existing well bonded resilient flooring which has been properly prepared. Existing adhesives must be scraped down to a smooth residue. Calcium Chloride (ASTM F1869) test results must not exceed 5 lbs., in-situ relative humidity readings (ASTM F2170) must not exceed 80%, and pH must be between 5.0 and 9.0. Do not use on chemically cleaned subfloors.

Site conditions, floor preparations, moisture, and alkalinity requirements should comply with those specified by the Carpet and Rug Institute. The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65° - 95°F, and the humidity below 65% for 48 hours prior to, during, and after the testing and installation.

**Clean-Up:** Clean up tools or spillage with water while adhesive is still wet. Fresh adhesive can be removed immediately with a damp cloth. When dry, remove with adhesive remover containing mineral spirits. Use mineral spirits sparingly. Do not penetrate seams. Mineral spirits will dissolve adhesive bond. Use with adequate ventilation.

**Open Time:** 20 to 30 minutes under normal conditions. High humidity and cold, and sealed or impervious substrates will extend open times.

**Coverage and Trowel Size:**

8 to 10 yards<sup>2</sup> per gallon, or 32 to 40 yards<sup>2</sup> per four gallon pail.

Trowel size: 1/8" x 1/8" x 1/16" V – notch

6 to 10 yards<sup>2</sup> per gallon, or 24 to 40 yards<sup>2</sup> per four gallon pail.

Trowel size: 1/8" x 1/8" x 1/16" U – notch

**Shelf Life:**

One year from manufacturing date, in an unopened container. This product is not photo chemically reactive as defined by California Rules 102 and 443. VOC content is below that established by California SCAQMD Rule 1168. 08/18/08

Technical Assistance: 1-800-387-9881 Option 2

- Wet Lay ●Antimicrobial ●Non-Flammable ●Non-Toxic ●Water Resistant
- Freeze/Thaw Stable ●Low Odor/Odorless When Dry

